


THERMAL GATE HOT RUNNER SYSTEMS


PRODUCT HIGHLIGHTS

- ❏ COMPACT THICKNESS : 70 MM (CLASS 1)
- ❏ NOZZLE TIP AND NOZZLE POSITION INDEXED
(WILL ALWAYS BE IN ITS ORIGINAL POSITION)
- ❏ SUPERIOR RHEOLOGY INSIDE THE MANIFOLD :
→ FREE MANIFOLD SHAPE
- ❏ HIGH PERFORMANCE TIP TECHNOLOGY FOR
AESTHETICAL OR GLASS FIBER REINFORCED
PARTS
 - **TECHTIP FOR ALL MATERIALS**
 - **PINPOINT OR FREEFLOW**
- ❏ AVAILABLE WITH OR WITHOUT CABLETRUNK



PIN POINT

- RECOMMENDED WHEN VESTIGE QUALITY IS CRITICAL
- PREVENT STRINGING



FREE FLOW

- RECOMMENDED FOR GLASS FIBER FILLED PLASTICS

RHEOLOGY : STANDARD DIAMETERS TO SUIT ALL INJECTION NEEDS


CLASS 1

NOZZLE A

- NOT AVAILABLE

NOZZLE B

- Ø 16, 18, 20 MM
- GATE Ø 3, 4, 5 MM



MANIFOLD

- Ø 10, 12, 14, 16, 18, 20 MM

NOZZLE C

- Ø 10, 12, 14 MM
- GATE Ø 2, 3, 4 MM

TOOL INTEGRATION : COMPACT DESIGN (CLASS 1 ONLY)

CLASS 1

**MANY STANDARD SOLUTIONS
HAVE BEEN DEVELOPED TO SUIT
ALL INJECTION SITUATIONS**

TECHNICAL MATERIALS

2K MOLDS

UNFAVORABLE L/Z RATIO

FAST COLOR CHANGE

